







**CONSTRUCTION NOTES**



**DATE ISSUED**  
 Issue Date



REVISIONS

| REV # | BY | DATE | DESCRIPTION |
|-------|----|------|-------------|
|       |    |      |             |
|       |    |      |             |
|       |    |      |             |
|       |    |      |             |
|       |    |      |             |
|       |    |      |             |

DRAWN: EH  
 DESIGNER: EH  
 REVIEWED: KCW

PROJECT #  
 24SM5586

**SCALES**

|                   |          |
|-------------------|----------|
| HORIZ:            | 1" = 30' |
| VERT:             | 1" = 30' |
| (24" x 36" SHEET) |          |

BAR SCALE MEASURES 1" ON A FULL SIZE SHEET, 0.5" FOR A HALF SIZE SHEET.



**PROJECT NAME:**  
 BLACK ICE

**PROJECT LOCATION:**  
 1400 N 300 W  
 SPANISH FORK, UTAH


**SHEET TITLE:**  
 DEMO PLAN

**PLAN SET:** PRELIM      **SHEET:** C1.0

**CONSTRUCTION NOTES**



**DATE ISSUED**  
Issue Date



REVISIONS

| REV # | BY | DATE | DESCRIPTION |
|-------|----|------|-------------|
|       |    |      |             |
|       |    |      |             |
|       |    |      |             |
|       |    |      |             |

DRAWN: EH  
DESIGNER: EH  
REVIEWED: KCW

PROJECT #  
24SM5586

**SCALES**

|                                      |                                     |
|--------------------------------------|-------------------------------------|
| HORIZ: 1" = 30'<br>(24" x 36" SHEET) | VERT: 1" = 10'<br>(24" x 36" SHEET) |
|--------------------------------------|-------------------------------------|

BAR SCALE MEASURES 1" ON A FULL SIZE SHEET, ADJUST FOR A HALF SIZE SHEET.




**PROJECT NAME:**  
**BLACK ICE**

**PROJECT LOCATION:**  
**1400 N 300 W  
SPANISH FORK, UTAH**

**SHEET TITLE:**  
**OVERALL SITE PLAN**


|                                   |                             |
|-----------------------------------|-----------------------------|
| <b>PLAN SET:</b><br><b>PRELIM</b> | <b>SHEET</b><br><b>C2.0</b> |
|-----------------------------------|-----------------------------|

CONSTRUCTION NOTES



DATE ISSUED

Issue Date



REVISIONS

| REV # | BY | DATE | DESCRIPTION |
|-------|----|------|-------------|
|       |    |      |             |
|       |    |      |             |
|       |    |      |             |
|       |    |      |             |
|       |    |      |             |
|       |    |      |             |

DRAWN: EH  
DESIGNER: EH  
REVIEWED: KCW

PROJECT #  
24SM5586

SCALES

HORIZ: 1" = 20'  
VERT: (24" x 36" SHEET)  
BAR SCALE MEASURES 1" ON A FULL SIZE SHEET, ADJUST FOR A HALF SIZE SHEET.

PROJECT NAME:

BLACK ICE

PROJECT LOCATION:

1400 N 300 W  
SPANISH FORK, UTAH

SHEET TITLE:

SITE PLAN



PLAN SET:

PRELIM


SHEET

C3.0

**CONSTRUCTION NOTES**



**DATE ISSUED**  
Issue Date



REVISIONS

| REV # | BY | DATE | DESCRIPTION |
|-------|----|------|-------------|
|       |    |      |             |
|       |    |      |             |
|       |    |      |             |
|       |    |      |             |

DRAWN: EH  
DESIGNER: EH  
REVIEWED: KCW

PROJECT #  
24SM5586

**SCALES**

|        |                   |   |    |
|--------|-------------------|---|----|
| HORIZ: | 1" = 30'          | 0 | 1" |
| VERT:  | (24" x 36" SHEET) |   |    |

BAR SCALE MEASURES 1" ON A FULL SIZE SHEET, ADJUST FOR A HALF SIZE SHEET.

**PROJECT NAME:**  
**BLACK ICE**


**PROJECT LOCATION:**  
**1400 N 300 W  
SPANISH FORK, UTAH**

**SHEET TITLE:**  
**UTILITY PLAN**

|                                   |                             |
|-----------------------------------|-----------------------------|
| <b>PLAN SET:</b><br><b>PRELIM</b> | <b>SHEET</b><br><b>C4.0</b> |
|-----------------------------------|-----------------------------|









- NOTES:**
1. INSPECT AND REPAIR FENCE AFTER EACH STORM EVENT; SEE PLAN VIEW.
  2. REMOVED SEDIMENT SHALL BE DEPOSITED TO AN AREA THAT WILL NOT CONTRIBUTE SEDIMENT OFF-SITE AND CAN BE PERMANENTLY STABILIZED.
  3. SILT FENCE SHALL BE PLACED ON SLOPE CONTOURS TO MAXIMIZE PONDING EFFICIENCY.


**A** SILT FENCE



**STANDARD DETAIL TRENCH W/ NATIVE BACKFILL**




**ALTERNATE DETAIL TRENCH W/ GRAVEL**




**B** LOD FENCE WITH PRIVACY SCREEN


- NOTES:**
1. FENCE IS TO BE MAINTAINED AT ALL TIMES AND SHALL BE REPAIRED IMMEDIATELY UPON NOTIFICATION BY THE OWNER OR OTHER AFFECTED PARTY.
  2. FENCE SHALL BE MAINTAINED AT ALL TIMES AND SHALL BE REPAIRED IMMEDIATELY UPON NOTIFICATION BY THE OWNER OR OTHER AFFECTED PARTY.
  3. FENCE SHALL BE MAINTAINED AT ALL TIMES AND SHALL BE REPAIRED IMMEDIATELY UPON NOTIFICATION BY THE OWNER OR OTHER AFFECTED PARTY.
  4. FENCE SHALL BE MAINTAINED AT ALL TIMES AND SHALL BE REPAIRED IMMEDIATELY UPON NOTIFICATION BY THE OWNER OR OTHER AFFECTED PARTY.
  5. FENCE SHALL BE MAINTAINED AT ALL TIMES AND SHALL BE REPAIRED IMMEDIATELY UPON NOTIFICATION BY THE OWNER OR OTHER AFFECTED PARTY.
  6. FENCE SHALL BE MAINTAINED AT ALL TIMES AND SHALL BE REPAIRED IMMEDIATELY UPON NOTIFICATION BY THE OWNER OR OTHER AFFECTED PARTY.
  7. FENCE SHALL BE MAINTAINED AT ALL TIMES AND SHALL BE REPAIRED IMMEDIATELY UPON NOTIFICATION BY THE OWNER OR OTHER AFFECTED PARTY.
  8. FENCE SHALL BE MAINTAINED AT ALL TIMES AND SHALL BE REPAIRED IMMEDIATELY UPON NOTIFICATION BY THE OWNER OR OTHER AFFECTED PARTY.
  9. FENCE SHALL BE MAINTAINED AT ALL TIMES AND SHALL BE REPAIRED IMMEDIATELY UPON NOTIFICATION BY THE OWNER OR OTHER AFFECTED PARTY.
  10. FENCE SHALL BE MAINTAINED AT ALL TIMES AND SHALL BE REPAIRED IMMEDIATELY UPON NOTIFICATION BY THE OWNER OR OTHER AFFECTED PARTY.




**C** PORTABLE TOILET



**D** REINFORCED CONSTRUCTION ENTRANCE



**MAINTENANCE:** ROCK CONSTRUCTION ENTRANCE THICKNESS SHALL BE CONSTANTLY MAINTAINED TO THE SPECIFIED DIMENSIONS BY ADDING ROCK. A STOCK PILE OF ROCK MATERIAL SHALL BE MAINTAINED ON SITE FOR THIS PURPOSE. DRAIN SPACE UNDER WASH RACK SHALL BE KEPT OPEN AT ALL TIMES. DAMAGE TO THE WASH RACK SHALL BE REPAIRED PRIOR TO FURTHER USE OF THE RACK. AT THE END OF EACH CONSTRUCTION DAY, ANY SEDIMENT DEPOSITED ON PAVED ROADWAYS SHALL BE REMOVED AND RETURNED TO THE CONSTRUCTION SITE.




- NOTES:**
1. EXCESS AND WASTE CONCRETE SHALL NOT BE WASHED INTO STREET OR INTO A DRAINAGE SYSTEM.
  2. FOR WASHOUT OF CONCRETE AND MORTAR PRODUCTS, A DESIGNATED CONTAINMENT FACILITY OF SUFFICIENT CAPACITY TO RETAIN LIQUID AND SOLID WASTE SHALL BE PROVIDED ON SITE.

**E** CONCRETE WASHOUT

**CONSTRUCTION NOTES**

**DATE ISSUED**  
Issue Date



| REVISIONS |    |      |             |
|-----------|----|------|-------------|
| REV #     | BY | DATE | DESCRIPTION |
|           |    |      |             |
|           |    |      |             |
|           |    |      |             |
|           |    |      |             |
|           |    |      |             |
|           |    |      |             |
|           |    |      |             |
|           |    |      |             |
|           |    |      |             |

DRAWN: EH  
DESIGNER: EH  
REVIEWED: KCW

PROJECT #  
24SM5586

| SCALES  |                   |
|---|-------------------|
| HORIZ:  | 0 1"              |
| VERT:   | (24" x 36" SHEET) |
| BAR SCALE MEASURES 1" ON A FULL SIZE SHEET, ADJUST FOR A HALF SIZE SHEET. |                   |


**PROJECT NAME:**  
**BLACK ICE**

**PROJECT LOCATION:**  
**1400 N 300 W  
SPANISH FORK, UTAH**


**SHEET TITLE:**  
**EROSION CONTROL  
DETAILS**

**PLAN SET:** PRELIM      **SHEET:** C7.0







A WATER SERVICE




B CURB & GUTTER




C FIRE HYDRANT




D SEWER MANHOLE




E SEWER SERVICE



F STORM INLET BOX



G THRUST BLOCK




H ASPHALT SECTION

CONSTRUCTION NOTES

DATE ISSUED

Issue Date



REVISIONS

| REV # | BY | DATE | DESCRIPTION |
|-------|----|------|-------------|
|       |    |      |             |
|       |    |      |             |
|       |    |      |             |
|       |    |      |             |

DRAWN: EH  
DESIGNER: EH  
REVIEWED: KCW

PROJECT #  
24SM5586

SCALES

HORIZ: 1" = 30'  
VERT: (24" x 36" SHEET)  
BAR SCALE MEASURES 1" ON A FULL SIZE SHEET, ADJUST FOR A HALF SIZE SHEET.

PROJECT NAME:

BLACK ICE

PROJECT LOCATION:

1400 N 300 W  
SPANISH FORK, UTAH

SHEET TITLE:

DETAILS

PLAN SET:


PRELIM

SHEET



D1.0

**Precast box**

- GENERAL**
  - The drawing shows typical pipe connections. Refer to construction drawings for connection locations or refer to field location of existing piping when engineering pipe connection to the box.
  - This drawing is acceptable where the water table elevation is less than 3 feet above the floor of the box. If elevation of water table is higher, engineering calculations and drawings must be submitted to and approved by the ENGINEER.
  - Submit bar design detail for ENGINEER'S review.
- PRODUCTS**
  - Base Course: Untreated base course, APWA Section 32 11 23. Do not use gravel as a base course without ENGINEER'S permission.
  - Backfill: Common fill, APWA Section 31 05 13. Maximum particle size 2-inches.
  - Precast Concrete: Class 4000 precast, APWA Section 03 40 00.
  - Reinforcement: Deformed, 60 ksi yield grade steel, ASTM A615. Coated steel is not required for small drainage structures shown on this drawing.
  - Frame and Cover (or Grate): Use the appropriate unit indicated in the Contract Documents.
  - Joint Sealant: Rubber-based, compressible.
- EXECUTION**
  - Concrete Placement: Provide 2-inches of concrete cover over reinforcing steel.
  - Lifting Points: Provide at least 2 lifting points per section that avoid interference with the reinforcing steel and that are designed according to PCI (Prestressed Concrete Institute) design handbook. Lift only from the engineered lifting points.
  - Depth: Drainage boxes and riser combinations that exceed 8-feet from finished grade to the bottom of the box requires ENGINEER'S approval. Submit design calculations and shop drawings.
  - Core Holes:
    - Provide core holes that are at least 4" larger than attaching outer pipe diameter. Cut core holes at the manufacturing plant unless ENGINEER permits field core holes.
    - Center core holes to leave 2" of concrete measured horizontally from inside wall of the box to core hole. Locate core hole vertically so bottom of core hole will be at or above floor elevation with at least 5-inches of concrete directly above the core hole to the top of the box.
    - Deviations from core hole tolerances require shop drawings. Shop drawings will identify lifting point number and location.
- Precast Top:** Design precast top for AASHTO HL-93 live loads and submit rebar detail and stamped design drawings to ENGINEER. Show connection detail for frame and grate or cover.




**T-12 Outlet Structures**



OS-10 Urban Drainage and Flood Control District August 2013  
Urban Storm Drainage Criteria Manual Volume 3

**T-12 Outlet Structures**



**ORIFICE PLATE NOTES:**

- MINIMIZE THE NUMBER OF COLUMNS.
- PROVIDE GASKET MATERIAL BETWEEN THE ORIFICE PLATE AND CONCRETE.
- BOLT PLATE TO CONCRETE 12" MAX. ON CENTER.

**TRASH RACKS:**

- WELL-SCREEN TRASH RACKS SHALL BE STAINLESS STEEL AND SHALL BE ATTACHED BY INTERMITTENT WELDS ALONG THE EDGE OF THE MOUNTING FRAME.
- BAR GRATE TRASH RACKS SHALL BE ALUMINUM AND SHALL BE BOLTED USING STAINLESS STEEL HARDWARE.
- TRASH RACK WIDTHS PROVIDED IN TABLE OS-2A AND OS-3A ARE FOR SPACED TRASH RACK MATERIAL AND NEED TO BE ADJUSTED FOR MATERIALS HAVING A DIFFERENT OPEN AREA/GROSS AREA RATIO (R VALUE).
- STRUCTURAL DESIGN OF TRASH RACKS SHALL BE BASED ON FULL HYDROSTATIC HEAD WITH ZERO HEAD DOWNSTREAM OF THE RACK.


**OVERFLOW TRASH RACKS:**

- ALL TRASH RACKS SHALL BE MOUNTED USING STAINLESS STEEL HARDWARE AND PROVIDED WITH HINGED AND LOCKABLE OR BOLTABLE ACCESS PANELS.
- TRASH RACKS SHALL BE STAINLESS STEEL, ALUMINUM, OR STEEL. STEEL TRASH RACKS SHALL BE HOT DIP GALVANIZED AND MAY BE HOT POWDER COATED AFTER GALVANIZING.
- TRASH RACKS SHALL BE DESIGNED SUCH THAT THE DIAGONAL DIMENSION OF EACH OPENING IS SMALLER THAN THE DIAMETER OF THE OUTLET PIPE.
- STRUCTURAL DESIGN OF TRASH RACKS SHALL BE BASED ON FULL HYDROSTATIC HEAD WITH ZERO HEAD DOWNSTREAM OF THE RACK.

**Figure OS-4. Orifice Plate and Trash Rack**

August 2013 Urban Drainage and Flood Control District August 2013 OS-11  
Urban Storm Drainage Criteria Manual Volume 3

**A STORM CLEAN OUT BOX**




**C OUTLET PLATE**

**B OUTLET STRUCTURE**

**CONSTRUCTION NOTES**

**DATE ISSUED**  
Issue Date



**REVISIONS**

| REV # | BY | DATE | DESCRIPTION |
|-------|----|------|-------------|
|       |    |      |             |
|       |    |      |             |
|       |    |      |             |

DRAWN: EH  
DESIGNER: EH  
REVIEWED: KCW

PROJECT #  
24SM5586

**SCALES**

HORIZ: 1" = 30'  
VERT: (24" x 36" SHEET)

0 1"  
BAR SCALE MEASURES 1" ON A FULL SIZE SHEET, ADJUST FOR A HALF SIZE SHEET.

**PROJECT NAME:**  
**BLACK ICE**

**PROJECT LOCATION:**  
**1400 N 300 W  
SPANISH FORK, UTAH**

**SHEET TITLE:**  
**DETAILS**

**PLAN SET:** PRELIM **SHEET** D2.0